



BEHR

REHAU Group

PRODUCT SPECIFICATIONS | KEEP COOL®

Valid for retrofit & OEM

| Product name: | KEEP COOL® Curve | KEEP COOL® Plane |
|-------------------------------|--|--|
| Variants: | KEEP COOL® Curve 625 KEEP COOL® Curve 1250 KEEP COOL® Curve Alu 625 KEEP COOL® Curve Alu 1250 KEEP COOL® Curve End Unit | KEEP COOL® Plane 625 KEEP COOL® Plane 1250 KEEP COOL® Plane Alu 625 KEEP COOL® Plane Alu 1250 KEEP COOL® Plane End Unit KEEP COOL® Plane Alu End Unit |
| Characteristics: | Curved glass Modern, elegant design Easy, ergonomic, customer friendly operation | Flat glass Discreet design Easy, ergonomic, customer friendly operation |
| Features: | Retrofit and OEM solutions. Customised to fit on all islands with parallel top edges. Unrestricted access to the entire island at all times. Easy operation (4 low friction sliding shoes on all glass panels for effortless gliding operation). | |
| Application: | Covers for ventilated horizontal display units in public sales and display areas. Works with coolers (≥ 0°C) and freezers (≥ -24°C. The panel heating must be switched on). Environment temperature must be under 24°C and 55% R.H. (Climate class 8). | |
| Limitations: | The covers are not designed to carry extra load. Do not place items on the covers, nor use them as display/shelf area. | |
| Dimensions: | The covers are manufactured to fit the dimensions of the horizontal display. The opening of 3-glass solutions: 625 mm modules: approx. 600 mm x 1/3 of the width of the island. 1250 mm modules: approx. 1225 mm x 1/3 of the width of the island. The opening of 2-glass solutions: 625 mm modules: approx. 600 mm x 1/2 of the width of the island. 1250 mm modules: approx. 1225 mm x 1/2 of the width of the island. The opening of 1-glass solutions: 625 mm modules and 1250 mm modules: Approx. half the width of the island (defined by the the width of the upper cabinet and the accessible area of the island). | |
| Weight: | One 625 mm glass weighs approx.: 2,5 Kg. One 1250 mm glass weighs approx.: 5 kg. | |
| Materials: | 4 mm single layer, low-e safety glass. Plastics (mostly PVC). Anodised aluminium. | |
| Colour: | Plastics: RAL 7015, RAL 7046 or RAL 9005. Gables (KEEP COOL® Curve): RAL 9006. | |
| Optionals (surcharge): | LED Price profiles: 1-sided and 2-sided 1-level and 3-levels A4 frames Clips for standard non-BEHR A4 frames Lock plates: RAL 7015, RAL 7046 or RAL 9005 Safety stops: RAL 7015, RAL 7046 or RAL 9005 | |
| Electrical: | Not available | |
| Expected life span: | 10 years or 300.000 openings. | |
| Savings: | Energy savings of up to 50% . | |
| Safety certificates: | Produced and tested according to General Product Safety Directive (2001/95/EC). Safety glass EN 12150 / ANSI Z97.1. | |
| Installation: | Delivered pre-fabricated and ready for installation. Fixed onto the top of the island with strong double coated tape. Fitting must be performed by professionals. | |
| Technical adjustments: | After installation, the air speed and the temperature of the freezer island must be adjusted and the frequency of the defrosting cycles reduced. Technical Adjustments instructions are delivered with the product. | |
| Care and cleaning: | Glass and sliding tracks must be cleaned regularly. Use a soft microfiber cloth and a mild cleaning agent (e.g. window cleanser). Do not use steam or high pressure water. Do not use harsh or abrasive detergents (e.g. solvent, acidic, ammoniac, chloric or oil based). A User Guide is delivered with the product. | |
| Warranty: | 24 months. Please refer to our Terms of Sales and Delivery. | |
| How to order: | Contact us for a measuring guide and a quote: sales@behr.dk | |



DISCLAIMER:

This product specification is not a complete guide to product usage. Further information is available from REHAU-BEHR A/S and from the User Guide and the Technical Adjustment Instructions. This specification sheet must be read in conjunction with the User Guide and the Technical Adjustment Instructions and all applicable statutory requirements. Product specifications may change without notice.